

## VHF/GPS-05

490015-T

Marine and Land Based VHF/GPS-GLONASS Antenna. Tx/Rx. 35W 0 dBd. N-female. N239F. 3.3-18VDC. Cable set BNC-m, TNC-m and UHF-m and filter. Packed in tube and box.

VHF/GPS is a VHF antenna with a helix GPS/GLONASS antenna for frequencies 1575.42 MHz & 1602 MHz incorporated. This antenna is manufactured in premium quality materials in order to prevent galvanic corrosion. Radiating elements are made of brass. The antenna is manufactured using crimping technology giving the antenna a 4-5 times stronger build-up. The swivel nut N239F is included for installation on ISO 228/1-G1 mounts. A cable set is included too, equipped with BNC-male, TNC-male and UHF-male connectors. The antenna is always subject for improvement. The antenna has the same rugged design as all other AC Antennas products thus it withstands harsh environmental...

### Short description

Product group	GPS
Design	Coaxial dipole with active positioning antenna
Pattern	Omnidirectional

### Electrical specifications

Frequency range [MHz]	A: 156-162.5/ B:1575.42/ C: 1602
Bandwidth [MHz]	6.5/0.01/0.01
Nominal Impedance [Ohm]	50
Max. Input Power [Watt]	A. 35 B+C: Receive only
Gain [dBd/dBi/Marine dB]	A: 0 / A: 2.15 / A: 3
VSWR	<2:1
Polarisation	
DC Shorted	No
DC Grounded	Yes
Connector	N-Female

### Mechanical specifications

Length [m/ft]	1.26 / 3.82
Sections	1
Weight [kg/lbs]	0.70 / 1.50
Survival Wind Speed [km/h / m/s / mph]	160 / 44 / 99
Wind Area [m2/ft2]	0.0227 / 0.2444
Wind Load @ 160km/h [N]	33
Material	Fibreglass
Colour	White
Operating Temperature Range [°C/°F]	-40 to +60 / -40 to +140
Ingress Protection	IP68
Thread	1" 14TPI male / ISO 228/1-G1 female
Mounting	Mounting nut included



